

CCTV Camera

VS-IE30T-70



Zoom Focus

*Effio-E + 673 CCD With OSD
OSD Button in the cable*




Features

- ◆ Weatherproof IR Camera
- ◆ SONY Exview HAD CCD II (ICX672/3AKA)
- ◆ 42 pcs $\varnothing$ 5mm IR-LED, IR Range 35M
- ◆ OSD/2D-DNR/BLC/MD/Privacy Masking
- ◆ 3-Axis Bracket, Hidden Cable Design
- ◆ Built-in 4--9mm Manual Zoom Lens



Size Chart



Specifications

Model Name	VS-IE30T-70
Image Device	1/3" Exview HAD CCD II (ICX672/3AKA)
DSP Device	Effio-E (CXD4127GG, CXD4816GG)
Resolution	Color Mode: 650TVL; B/W Mode: 700TVL
Picture Elements	PAL: 976(H) × 582(V) NTSC: 976(H) × 494(V)
IR Led & IR Range	42pcs $\varnothing$ 5 IR Led; 35M IR Distance
Min. Illumination	0.001 Lux (F2.0)/ 0 Lux IR On
Lens Furnished	Built-in 4--9mm Manual Zoom Lens (2.8--12mm Optional)
TV System	PAL/NTSC
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50~1/110,000
S/N Ratio	More than 52dB
Gamma	0.45
Exposure	Auto
Shuter/ AGC	Auto/Manual
White Balance	ATW / User1/User2
Backlight	OFF/ON/BLC/ HLC
Pict Adjust	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
ATR	ON/OFF
Motion Det	OFF/ON (Detect sense/ Area Sel)
Peivacy Masking	OFF/ON (4 Zone)
Day/Nigh	True Day and Night (Auto/ Day / Night / Ext. D&N)
2D-NR	OFF/ON (Y/C level)
Camera ID	OFF/ON
Sync. System	Internal
Waterproofing Criterion	IP 66

Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V±10%
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Dimension	199(L)x97.4(W)x181.8(H) mm
Weight	1500g

Design and specifications are subject to change without notice.