

PTZ Camera

VS-FG69 Series



with OSD menu



Features

- ◆ High Speed Dome camera
- ◆ Preset speed: 400°/Sec, 360°Continue
- ◆ Preset points: 128 Points
- ◆ Operation menu: Multi-Language

Specifications

Model Name	VS-FG691	VS-FG692
Indoor/Outdoor Type	Indoor dome	Outdoor dome
Address	0~255	
Pan range	360°Continue	
Tilt range	0°~90° Flip	
Manual speed Pan	0.1~300°/Sec	
Manual speed Tilt	0.1~120°/Sec	
Preset speed	400°/Sec	
Preset accuracy	±0.10°	
Preset points	128 Points	
Operation menu	Multi-Language (English chinese German etc.)	
Function display	Yes	
Operation crosshair function	Yes	
Pan and Tilt position display	Yes	
Privacy zones(Masking)	8 Programable Zones	
Sector label display	8 Programable Zones	
Recall Function	Yes	
Operation return function	Yes	
PTZ Tours(Pattern)	3 Programable (Pan/Tilt/Zoom and each tour is 120 seconds)	
Vector scan groups	6 Programable(Dwell time speed preset point)	
Integrate multi-protocol	Pelco_D/P	
Auto Scan	with Smart Programable variable speed	
High efficient 3-dimension scan	Yes	
Long-focus speed-limited	Yes	
Intelligent power off real time memory	Yes	
Home position	Yes	
Supporting camera	Automatically detect 8 kinds of camera(Sony, Hitachi, Yoko, CNB, Sanyo, LG, Hitron and Samsung)	
Camera menu operation	Yes	
Manual operation	Endless	
IP66 for outdoor use	No	
Operating Temperature	0℃~50℃	
Humidity	0%~90% (Non condensing)	
Heater in operate	No	
Power	15VDC 2A	24VAC 2A 60Hz/50Hz
Consumption	18W	20W
Communication	RS485 (+/-)	
Connection	RJ45 cable	BNC cable

Design and specifications are subject to change without notice.