

PTZ Camera

VS-LN5.P Series



with OSD menu



Features

- ◆ Mini High Speed Dome
- ◆ Preset speed: 300°/Sec, 360°Continue
- ◆ Preset points: 128 Points
- ◆ Supporting camera: 10×zoom
- ◆ Operation menu: Multi-Language

Specifications

Model Name	VS-LN51P	VS-LN52P
Address	0~255	
Pan range	360°Continue	
Tilt range	0°~90° Flip	
Manual speed Pan	0.1~240°/Sec	
Manual speed Tilt	0.1~120°/Sec	
Preset speed	300°/Sec	
Preset accuracy	±0.10°	
Preset points	128 Points	
Operation menu	Multi-Language (English chinese etc.)	
Function display	Yes	
Operation crosshair function	Yes	
Pan and Tilt position display	Yes	
Sector label display	8 Programable Zones	
Recall Function	Yes	
Operation return function	Yes	
Vector scan groups	6 Programable(Dwell time speed preset point and embed other vector scan)	
Integrate multi-protocol	Pelco_D/P	
Auto Scan	with Smart Programable variable speed	
High efficient 3-dimension scan	Yes	
Long-focus speed-limited	Yes	
Intelligent power off real time memory	Yes	
Home position	Yes	
Supporting camera	Optical X10(Samsung Hitachi Sony etc)	
Camera menu operation	Yes	
Manual operation	Endless	
IP66 for outdoor use	No	
Operating Temperature	-30℃~60℃	
Humidity	0%~90% (Non condensing)	
Power	24VAC 1000mA 60Hz/50Hz	
Consumption	6W	
Communication	RS485 (+/-)	
Connection	BNC cable	

Design and specifications are subject to change without notice.