

PTZ Camera

VS-PM69 Series



with OSD menu and Alarm

Features

- ◆ High Speed Dome camera
- ◆ Preset speed: 400°/Sec, 360°Continue
- ◆ Preset points: 128 Points
- ◆ Operation menu: Multi-Language
- ◆ With Alarm function

Specifications

Model Name	VS-PM691	VS-PM692
Indoor/Outdoor Type	Indoor dome	Outdoor dome
Address	0~255	
Pan range	360°Continue	
Tilt range	0°~90°Flip	
Manual speed Pan	0.1~300°/Sec	
Manual speed Tilt	0.1~120°/Sec	
Preset speed	400°/Sec	
Preset accuracy	±0.10°	
Preset points	128 Points	
Operation menu	Multi-Language (English chinese German,French,Russian,Italian,Spanish.)	
Function display	Yes	
User admin	Master/Operator password setup and operation lock setup	
Operator Authorization	Authorization of operator programming	
Date/Time setup and display	Date/time display on screen and modify	
Assignment Programming	8 assignments programming,operation mode,function matter setup etc.	
Power Timer Programming	Power ON/OFF and Mode setup	
Alarm in Programming	8 inputs,normality setup,Notice Label display,Trigger or recall function,Prior,Operation time setup	
Alarm out Programming	2 outputs,4 triggers,Label display,Operation time setup etc.	
Temperature setup and display	Temperature alarm, Notice Label display and temperature display on screen	
Operation crosshair function	Yes	
Pan and Tilt position display	Yes	
Privacy zones (Masking)	8 Programable Zones	
Sector label display	8 Programable Zones	
Recall Function	Yes	
PTZ Tours (Pattern)	3 Programable (Pan/Tilt/Zoom and each tour is 120 seconds)	
Operation return function	Yes	
Vector scan groups	6 Programable(Dwell time speed preset point and embed other vector scan or PTZ tours)	
Integrate multi-protocol	Pelco_D/P	
Auto Scan	with Smart Programable variable speed	
High efficient 3-dimension scan	Yes	
Long-focus speed-limited	Yes	
Intelligent power off real time memory	Yes	
Home position	Yes	
Supporting camera	Automatically detect 8 kinds of camera(Sony, Hitachi, Yoko, CNB, Sanyo, LG, Hitron and Samsung)	
Camera menu operation	Yes	
Manual operation	Endless	
IP66 for outdoor use	No	Yes
Operating Temperature	0℃~50℃	-30℃~60℃
Humidity	0%~90% (Non condensing)	
Heater in operation	No	6℃ on 14℃ off
Power	24VAC 2A 60Hz/50Hz	
Consumption	20W	35W
Communication	RS485 (+/-)	
Connection	BNC cable	

Design and specifications are subject to change without notice.